

MATERIALS LIST - TIMBER

Section 1 - Timber required for hull construction. This does not include the material required for construction of Coxes seat and bow seat, though these can be probably be made up from off cuts.

The fitlins or stretchers or footrests are not included - these are "open design" and it is up to the builder to construct what they think is the best arrangement.

Unless otherwise mentioned, all timber should be entirely clear of knots. Lengths given are the bare minimum; timber should be purchased with some excess to allow for scarphs, shakes, etc.

Part	X-section	Tot Len	Material	Comments
Hog	1½" x 4"	17	Larch	May be made in 2 parts with scarph. Some small knots are acceptable.
Keel	1¾" x 2¾"	17	Larch	May be made in 2 parts with scarph. Some small knots are acceptable
Stems - Sawn	2" x 4"	32	Larch	
Stems - Laminated	2¼" x 5/16"	170	Larch	28 off 6'6" lengths
Beams	1¼" x 2½"	20	Larch	4 off 5'
Thwarts (Tafts)	7/8" x 8"	20	Larch	4 off 5' Some small knots are acceptable
Gunwales	5/8" x 1¾"	130	Larch	10 off 12-13ft lengths
Rouths	1" x 2½"	12	Oak	
Kabes	¾" x 3"	6	Oak	
Oars	2¼" x 2¼"	52	Larch, Dfir, Ash	4 off 13ft Must be fine grained & clear.
Sclates	2 ¾" x ½"	16	Oak	

Section 2 - Timber required to complete the hull as shown in designer's drawings, builder to check quantities. Please see the outline rules of boat construction.

Bottom boards	3/4 x 6"	+ - 60	Red Pine	
Spine	3/4" x 2-1/2"	16	Red Pine	
Deckbeams	3/4" x 1-3/4"	30	DFir/Larch	
Kingplank	1-1/8" x 2-1/2"	8	DFir/Larch	
Gunwale Rubbing Strip	5/8" x 1"	60	Oak/Elm	